



## CLASSIC SUMMIT

1.5mx1.5m / 2.4mx2.4m / 3mx3m  
3mx4.5m / 3mx6m / 5mx5m / 6mx6m


CLASSIC RANGE




ITEMS	SPECIFICATION						
Size	1.5x1.5	2.4x2.4	3x3m	3x4.5m	3x6m	5x5m	6x6m
Height	2.99m	2.99m	3.29m	3.29m	3.29m	4.13m	3.84m
Clearance	2m	2m	2m	2m	2m	2.13m	2m
Frame Box Dimensions	163x30x30cm	163x35x36cm	163x28x28cm	163x40x27cm	163x50x27cm	175x56x56cm	175x56x56cm
Frame Weight	22kg	27kg	29kg	39kg	53kg	70kg	110kg
Roof Weight	POLY 4kg PVC 5kg	5kg 8kg	7kg 11kg	10kg 17kg	13kg 19kg	16kg 24kg	20kg -
Main Profile	40 x 40 x 2mm						
Truss Bars	32 x 16 x 1415mm						
Framework	Aluminium 6005/T5 T6063 / Reinforced Aluminium Inner Leg						
Pull Ring System	Yes						
Roof Tension	Spring						
Nuts & Bolts	Stainless Steel						
Connectors	Extruded Aluminium						
Feet	Zinc Coated Steel 100 x 100mm						
Fabric	Plain 500D PVC Coated Polyester  Printed 600D PU Coated Polyester 580GSM PVC						
Includes	Tie Down Ropes, Steel Pins & Wheeled Protective Cover*						
Manufacturer's Warranty	Frame 7 Year / Polyester Fabric 1 Year Plain PVC 5 Year / Printed PVC 2 Year / Clear PVC 2 Year						

### TECHNICAL DIAGRAMS


Type:  
1.5mx1.5m




Type:  
2.4mx2.4m




Type:  
3mx3m




Type:  
3mx 4.5m




Type:  
3mx6m



Type:  
5mx5m



Type:  
6mx 6m



### ADDITIONAL INFORMATION

The Classic Summit is the Extreme Marquees signature range. Available since 2004, the strength and durability outperforms the rest and the Summit is the preferred marquee frame for many of our customers.

This commercial range is proven to be reliable for the demands of professional use and withstands years of use within leisure groups and clubs.

The Summit original range features a solid 40mm square frame type, extruded aluminum connectors, reinforced inner legs, available in seven sizes, up to ten roof colours and custom printing available from a single valance print all the way up to full custom digitally printed roof and wall packages.

### FRAME DETAIL



40mm Frame Profile



Aluminum Connectors



Oversized Truss Bars



Roof Tensioning



Pull Ring Height Adjustment



Commercial Feet